

Benne à béton 1021 – vidage déporté



Forme cylindro-conique à déversement déporté.
Conception robuste., commandée par levier.
Version standard: chaînes soudées certifiées.

Alternative sur demande : Anse (si ≥ 750 l avec palonnier), ou anneaux de levage.

Option sur demande: Fourreau uniprise – 2 côtés

Type	Vol.	D	S	A	H1	H2	H	HB	kg
1021.1	150	820	820	340	940	100	1165	1340	80
1021.2	200	820	820	380	940	200	1265	1510	92
1021.3	250	820	820	380	940	250	1315	1590	105
1021.4	300	820	820	380	940	300	1364	1640	120
1021.5	350	970	970	420	1150	150	1425	1700	130
1021.6	375	970	970	420	1150	200	1475	1750	140
1021.7	400	970	970	420	1150	250	1525	1800	150
1021.8	500	970	970	420	1150	350	1605	2000	162
1021.9	600	970	970	420	1150	450	1725	2100	180
1021.10	750	1150	1150	480	1270	350	1745	2100	230
1021.11	800	1150	1150	480	1270	450	1770	2150	245
1021.12	1000	1300	1340	500	1330	350	1780	2300	275
1021.13	1250	1400	1440	500	1400	400	1860	2450	358
1021.14	1500	1400	1440	500	1400	600	2060	2600	405
1021.15	1750	1600	1600	500	1600	400	2060	2800	446
1021.16	2000	1600	1600	500	1600	550	2210	2950	465
1021.17	2500	1800	1800	600	1800	400	2320	3000	620
1021.18	3000	1800	1800	600	1800	600	2520	3200	760
1021.19	3500	1800	1800	600	1800	800	2730	3400	870
1021.20	4000	1800	1800	600	1800	1000	2930	3600	990

HB* = hauteur benne avec anse/palonnier compris

