

Fusées à tête fixe

Tête remplaçable et fusée monobloc



LA FUSÉE QUI A COMMENCÉ LA RÉVOLUTION
DU SANS TRANCHÉE... EFFICACE ET D'UNE
GRANDE FIABILITÉ DANS LA PLUPART DES
TYPES DE SOL.

Modèle	Réf.	Réf. Kit US	Réf. Kit EU	Diamètre in (mm)	Longueur in (mm)	Poids lb (kg)	Air cfm (L/min)	Vis arrière	Pression psi (bar)
2.00" (50) RH-SR	20222	20222-1	20222-2	2.06 (50)	45.3 (115)	28 (13)	22 (623)	4	110 (7.6)
2.00" (50) RH-PP-BL	21733	21733-1	21733-2	2.06 (50)	39.0 (99.1)	24 (11)	18 (510)	n/a	110 (7.6)
2.50" (67) RH-SR	25222	25222-1	25222-2	2.64 (67)	48.25 (122.6)	50 (23)	31 (878)	4	110 (7.6)
2.50" (67) RH-PP-Df	25522	25522-1	25522-2	2.64 (67)	48.25 (122.6)	50 (23)	31 (878)	4	110 (7.6)
2.50" (67) RH-PP-SW-Df	26622	26622-1	26622-2	2.64 (67)	33.9 (86.1)	31 (14)	21.5 (609)	4	110 (7.6)
3.00" (75) RH-SR	30222	30222-1	30222-2	3.00 (75)	52.18 (132.5)	67 (30)	32 (906)	4	110 (7.6)
3.00" (75) RH-PP-Df	31222	31222-1	31222-2	3.00 (75)	51.7 (131.3)	67 (30)	35 (991)	4	110 (7.6)
3.00" (75) RH-PP-SW-Df	31622	31622-1	31622-2	3.00 (75)	41.6 (105.7)	50 (23)	33 (934)	4	110 (7.6)
3.50" (89) RH-PP-Df	35022	35022-1	35022-2	3.50 (89)	59.0 (149.9)	94 (43)	53.5 (1,515)	5	110 (7.6)
4.00" (98) RH-PP-Df	40422	40422-1	40422-2	3.88 (98.43)	62.8 (159.5)	131 (59)	64 (1,812)	6	110 (7.6)
4.00" (98) RH-SR	38222	38222-1	38222-2	3.88 (98)	63.95 (162.4)	136 (62)	68 (1,926)	6	110 (7.6)
5.125" (130) SR	51222	51222-1	51222-2	5.125 (133)	65.92 (167.4)	214 (97)	98 (2,775)	8	110 (7.6)
5.125" (130) PP-Df	51422	51422-1	51422-2	5.25 (133.4)	64.8 (164.6)	244.8 (111)	160 (4,531)	8	110 (7.6)
5.50" (140) SR-BU	58222	58222-1	58222-2	5.50 (140)	63.95 (162.4)	170 (77)	68 (1,926)	6	110 (7.6)
5.625" (143) PP-BU-Df	51722	51722-1	51722-2	5.63 (142.9)	64.8 (164.6)	247.9 (113)	160 (4,531)	8	110 (7.6)
5.75" (145) SR	60222	60222-1	60222-2	5.88 (149)	79.5 (201.9)	305 (138)	132 (3,738)	8	110 (7.6)

RH-Tête remplaçable, SR-6 tours, PP-1/4 de tour, SW-Courte, BL-Sans vis, DF-Anti-débris, BU-Bulbée

COMPRIS DANS LE KIT



Fusée, huileur, flexible et raccords